

PRIME GLOBAL PARTNERS

PROFESSIONAL REFRIGERATION EQUIPMENT



Prime Global Partners

Commercial Refrigeration Equipment Catalog

Private-label sourcing, product development and brand-building for foodservice equipment distributors.



Prefer not to build your own brand? We also supply under our own Prime Refrigeration product line.

www.pgpsupply.com
sales@pgpsupply.com

Commercial Refrigeration Equipment

REACH-IN SERIES

[p.6-12](#)



[p.7](#)
PR1S / PR2S / PR3S



[p.8](#)
PF1S / PF2S / PF3S



[p.9](#)
PR12 / PF12



[p.10](#)
PR19 / PF19



[p.11](#)
PR35 / PF35



[p.12](#)
PR1G / PR2G / PR3G

REFRIGERATED SALAD/SANDWICH PREP TABLE

[p.13-17](#)



[p.14](#)
PS1 / PS2-36 / PS2-47 / PS2-60 / PS3



[p.16](#)
PS1M / PS2M-36 / PS2M / PS2M-60 / PS3M

REFRIGERATED PIZZA PREP TABLE

[p.18-19](#)



[p.19](#)
PP1 / PP2 / PP3

CHEF BASE REFRIGERATOR

[p.20-21](#)



[p.21](#)
PCB36 / PCB48 / PCB52 / PCB60 / PCB72 / PCB84

Table of Contents (cont.)

UNDERCOUNTER COOLER / FREEZER

p.22-24



[p.23](#)
PU27R / PU48R / PU60R /
PU72R



[p.24](#)
PU27F / PU48F / PU60F

WORK TOP COOLER / FREEZER

p.25-27



[p.26](#)
PWT27R / PWT48R / PWT60R /
PWT72R



[p.27](#)
PWT27F / PWT48F / PWT60F

BACKBAR COOLER / BEER DISPENSER

p.28-34



[p.29](#)
PBB24-48G / PBB24-60G /
PBB24-72G



[p.30](#)
PBB24-48S / PBB24-60S /
PBB24-72S



[p.31](#)
PDD24-48 / PDD24-60 / PDD24-
72



[p.32](#)
PDD1 / PDD2 / PDD3 / PDD4



[p.33](#)
PBB1G / PBB2G / PBB3G /
PBB4G



[p.34](#)
PBB1S / PBB2S / PBB3S /
PBB4S

HORIZONTAL BOTTLE COOLER

p.35-36



[p.36](#)
PBC26 / PBC36 / PBC50 /
PBC65 / PBC95

Table of Contents (cont.)

HORIZONTAL BEER FROSTER

p.37-38



[p.38](#)
PBF26-SZ / PBF36-SZ / PBF50-SZ / PBF65-SZ / PBF80-SZ / PBF95-SZ

GLASS FROSTER

p.39-40



[p.40](#)
PGF26 / PGF36 / PGF50

REFRIGERATED DELI CASE

p.41-43



[p.42](#)
PDC36-SS / PDC47-SS / PDC64-SS / PDC82-SS



[p.43](#)
PDCDT50 / PDCDT71 / PDCDT84

MERCHANDISER REFRIGERATOR

p.44-49



[p.45](#)
PMR24-1A / PMR24-1B



[p.46](#)
PMR21-1 / PMR26-1 / PMR25-1 / PMR28-1



[p.47](#)
PMR53-2Y



[p.48](#)
PMR48-2 / PMR53-2 / PMR78-3



[p.49](#)
PMR29-1 / PMR54-2 / PMR79-3

MERCHANDISER FREEZER

p.50-52



[p.51](#)
PMF26-1 / PMF27-1 / PMF31-1 / PMF49-2 / PMF53-2 / PMF79-3

Table of Contents (cont.)

AIR COOLED ICEMACHINE

p.53-54



p.54
PIM280-H / PIM350-H / PIM530-H

OPEN AIR MERCHANDISER

p.55-57



p.56
POAM30 / POAM36 / POAM48 / POAM72



p.57
POAM30G / POAM36G / POAM48G / POAM72G

REFRIGERATED CAKE DISPLAY CASE

p.58-60



p.59
PCD36-2 / PCD47-2 / PCD59-2 / PCD71-2



p.60
PCD36-3 / PCD47-3 / PCD59-3 / PCD71-3

MILK COOLER

p.61-62



p.62
PMC34 / PMC49 / PMC58

OUTDOOR RATED SMALL REFRIGERATOR

p.63-64



p.64
POR23-1



1 / 18

REACH-IN SERIES

Solid and glass door reach-in refrigerators and freezers built in heavy-duty stainless steel for precise, safe holding temperatures.

PR1S

PR2S

PR3S

PF1S

PF2S

PF3S

PR12

PF12

PR19

PF19

PR35

PF35

PR1G

PR2G

PR3G

Reach-In Solid Door Refrigerator



- ❖ Stainless steel interior and exterior, aluminum back. Option of bright white aluminum interior available.
 - ❖ Refrigeration system keeps food at safe temperatures between 33°F and 40°F (0.5°C to 5°C).
 - ❖ Self-Closing doors with 90 degree stay-open feature. Locks and keys included.
 - ❖ Shelves: Adjustable heavy-duty PVC coated shelves.
 - ❖ Preinstalled heavy-duty casters with brakes.
- ❖ Electronic control system makes it easy to adjust temperature set point and defrost frequency.
 - ❖ Removable installation board makes it easy to access condenser coil for cleaning and service.
 - ❖ Option of different handles & control panels available.
 - ❖ These units use HYDRO-CARBON R290 refrigerant, which is environmentally friendly and more efficient than R134a/R404a refrigerant.

MODEL	DOORS	SHELVES	DIMENSIONS (WxDxH)	CAPACITY	HP	AMPS	VOLTAGE	PLUG TYPE
PR1S	1	3	29 x 32 1/4 x 82 1/2 in 736 x 818 x 2095 mm	23 cu.ft. 650 L	1/3	3.6	115/60/1	NEMA 5-15P
PR2S	2	6	54 x 32 1/4 x 82 1/2 in 1371 x 818 x 2095 mm	47 cu.ft. 1321 L	1/2	6.2	115/60/1	NEMA 5-15P
PR3S	3	9	80 7/8 x 32 1/4 x 82 1/2 in 2054 x 818 x 2095 mm	72 cu.ft. 2040 L	4/5	7.2	115/60/1	NEMA 5-15P

Reach-In Solid Door Freezer



PF1S

PF2S

PF3S

- ❖ Stainless steel interior and exterior, aluminum back. Option of bright white aluminum interior available.
 - ❖ Refrigeration system keeps food at safe temperatures between -8°F and 0°F (-22°C to -18°C).
 - ❖ Self-Closing doors with 90 degree stay-open feature. Locks and keys included.
 - ❖ Shelves: Adjustable heavy-duty PVC coated shelves.
 - ❖ Preinstalled heavy-duty casters with brakes.
- ❖ Electronic control system makes it easy to adjust temperature set point and defrost frequency.
 - ❖ Removable installation board makes it easy to access condenser coil for cleaning and service.
 - ❖ Option of different handles & control panels available.
 - ❖ These units use HYDRO-CARBON R290 refrigerant, which is environmentally friendly and more efficient than R134a/R404a refrigerant.

MODEL	DOORS	SHELVES	DIMENSIONS (WxDxH)	CAPACITY	HP	AMPS	VOLTAGE	PLUG TYPE
PF1S	1	3	29 x 32 1/4 x 82 1/2 in 736 x 818 x 2095 mm	23 cu.ft. 650 L	2/3	4.2	115/60/1	NEMA 5-15P
PF2S	2	6	54 x 32 1/4 x 82 1/2 in 1371 x 818 x 2095 mm	47 cu.ft. 1321 L	1 2/7	8.5	115/60/1	NEMA 5-15P
PF3S	3	9	80 7/8 x 32 1/4 x 82 1/2 in 2054 x 818 x 2095 mm	72 cu.ft. 2040 L	1 1/2	14.4	115/60/1	NEMA 5-20P

Reach-In Refrigerator & Freezer



PR12



PF12

- ✳ Stainless steel door and exterior sides, aluminum back. Bright white aluminum interior.
 - ✳ Refrigeration system keeps food at safe temperatures.
 - ✳ Self-Closing doors with 90 degree stay-open feature. Locks and keys included.
 - ✳ Shelves: Adjustable heavy-duty PVC coated shelves.
- ✳ Electronic control system makes it easy to adjust temperature set point and defrost frequency.
 - ✳ Preinstalled heavy-duty casters with brakes.
 - ✳ Removable installation board makes it easy to access condenser coil for cleaning and service.
 - ✳ Option of different handles & control panels available.

MODEL	TEMP	SHELVES	DIMENSIONS (WXDXH)	CAPACITY	HP	AMPS	VOLTAGE	PLUG TYPE
PR12	33°F ~ 40°F	3	24 4/5 x 23 1/2 x 63 5/7 in 630 x 595 x 1619 mm	11 cu.ft. 315 L	1/3	3.1	115/60/1	NEMA 5-15P
PF12	-8°F ~ 0°F	3	24 4/5 x 23 1/2 x 63 5/7 in 630 x 595 x 1619 mm	11 cu.ft. 315 L	2/3	4.7	115/60/1	NEMA 5-15P

Economic Reach-In Refrigerator & Freezer



PR19



PF19

- ❖ Stainless steel door and exterior sides, aluminum back. Bright white aluminum interior.
 - ❖ Refrigeration system keeps food at safe temperatures.
 - ❖ Self-Closing doors with 90 degree stay-open feature. Locks and keys included.
 - ❖ Shelves: Adjustable heavy PVC coated shelves.
 - ❖ Preinstalled heavy-duty casters with brakes.
- ❖ Electronic control system makes it easy to adjust temperature set point and defrost frequency.
 - ❖ Removable installation board makes it easy to access condenser coil for cleaning and service.
 - ❖ These units use HYDRO-CARBON R290 refrigerant, which is environmentally friendly and more efficient than R134a/R404a refrigerant.

MODEL	TEMP	SHELVES	DIMENSIONS (WXDXH)	CAPACITY	HP	AMPS	VOLTAGE	PLUG TYPE
PR19	33°F ~ 40°F	3	29 x 25 1/2 x 82 1/2 in 736 x 648 x 2095 mm	17 cu.ft. 490 L	1/3	3.1	115/60/1	NEMA 5-15P
PF19	-8°F ~ 0°F	3	29 x 25 1/2 x 82 1/2 in 736 x 648 x 2095 mm	17 cu.ft. 490 L	2/3	3.8	115/60/1	NEMA 5-15P

Reach-In Refrigerator & Freezer



PR35



PF35

- ✱ Stainless steel door and exterior sides, aluminum back. Bright white aluminum interior.
 - ✱ Refrigeration system keeps food at safe temperatures.
 - ✱ Self-Closing doors with 90 degree stay-open feature. Locks and keys included.
 - ✱ Shelves: Adjustable heavy-duty PVC coated shelves.
- ✱ Electronic control system makes it easy to adjust temperature set point and defrost frequency.
 - ✱ Preinstalled heavy-duty casters with brakes.
 - ✱ Removable installation board makes it easy to access condenser coil for cleaning and service.
 - ✱ Option of different handles & control panels available.

MODEL	TEMP	SHELVES	DIMENSIONS (WxDxH)	CAPACITY	HP	AMPS	VOLTAGE	PLUG TYPE
PR35	33°F ~ 40°F	6	39 1/2 x 29 1/2 x 82 1/2 in 1004 x 750 x 2095 mm	27.2 cu.ft. 782 L	1	7.8	115/60/1	NEMA 5-15P
PF35	-8°F ~ 0°F	6	39 1/2 x 29 1/2 x 82 1/2 in 1004 x 750 x 2095 mm	27.2 cu.ft. 782 L	1	7.8	115/60/1	NEMA 5-15P

Reach-In Glass Door Refrigerator



PR1G



PR2G



PR3G

- ❖ Stainless steel interior and exterior, aluminum back. Option of bright white aluminum interior available.
 - ❖ Refrigeration system keeps food at safe temperatures between 33°F and 40°F (0.5°C to 5°C).
 - ❖ Self-Closing glass doors with locks and keys.
 - ❖ Shelves: Adjustable heavy-duty PVC coated shelves.
 - ❖ Preinstalled heavy-duty casters with brakes.
- ❖ Electronic control system makes it easy to adjust temperature set point and defrost frequency.
 - ❖ Removable installation board makes it easy to access condenser coil for cleaning and service.
 - ❖ Option of different handles & control panels available.
 - ❖ These units use HYDRO-CARBON R290 refrigerant, which is environmentally friendly and more efficient than R134a/R404a refrigerant.

MODEL	DOORS	SHELVES	DIMENSIONS (WDXH)	CAPACITY	HP	AMPS	VOLTAGE	PLUG TYPE
PR1G	1	3	29 x 32 1/4 x 82 1/2 in 736 x 818 x 2095 mm	23 cu.ft. 650 L	1/3	3.6	115/60/1	NEMA 5-15P
PR2G	2	6	54 x 32 1/4 x 82 1/2 in 1371 x 818 x 2095 mm	47 cu.ft. 1321 L	1/2	6.2	115/60/1	NEMA 5-15P
PR3G	3	9	80 7/8 x 32 1/4 x 82 1/2 in 2054 x 818 x 2095 mm	72 cu.ft. 2040 L	4/5	8.5	115/60/1	NEMA 5-15P



2 / 18

REFRIGERATED SALAD/SANDWICH PREP TABLE

Stainless steel sandwich and salad prep tables with refrigerated rail pans, sized from single-door to mega-top configurations.

PS1

PS2-36

PS2-47

PS2-60

PS3

PS1M

PS2M-36

PS2M

PS2M-60

PS3M

Sandwich/Salad Prep Table

PAGE 1 OF 2



PS1



PS2-36



PS2-47

- ✱ Stainless steel interior and exterior, aluminum back. Option of bright white aluminum interior available.
 - ✱ Refrigeration system keeps food at safe temperatures between 33°F and 40°F (0.5°C to 5°C).
 - ✱ Self-Closing doors with 90 degree stay-open feature. Locks and keys included.
 - ✱ Shelves: Adjustable heavy-duty PVC coated shelves.
 - ✱ Cutting boards and pans available.
- ✱ Preinstalled heavy-duty casters with brakes.
 - ✱ Electronic control system makes it easy to adjust temperature set point and defrost frequency.
 - ✱ Removable installation board makes it easy to access condenser coil for cleaning and service.
 - ✱ Option of different handles available.
 - ✱ These units use HYDRO-CARBON R290 refrigerant, which is environmentally friendly and more efficient than R134a/R404a refrigerant.

MODEL	DOORS	SHELVES	DIMENSIONS (WXDXH)	CAPACITY	HP	AMPS	VOLTAGE	PLUG TYPE
PS1	1	1	27 1/2 x 29 1/2 x 42 3/8 in 698 x 750 x 1075 mm	5.7 cu.ft. 160 L	1/4+	3.6	115/60/1	NEMA 5-15P
PS2-36	2	2	36 1/4 x 29 1/2 x 42 3/8 in 920 x 750 x 1075 mm	7.6 cu.ft. 213 L	1/4+	4.3	115/60/1	NEMA 5-15P
PS2-47	2	2	46 7/8 x 29 1/2 x 42 3/8 in 1188 x 750 x 1075 mm	9.5 cu.ft. 268 L	1/3	4.9	115/60/1	NEMA 5-15P

Sandwich/Salad Prep Table

PAGE 2 OF 2



PS2-60



PS3

- ❖ Stainless steel interior and exterior, aluminum back. Option of bright white aluminum interior available.
 - ❖ Refrigeration system keeps food at safe temperatures between 33°F and 40°F (0.5°C to 5°C).
 - ❖ Self-Closing doors with 90 degree stay-open feature. Locks and keys included.
 - ❖ Shelves: Adjustable heavy-duty PVC coated shelves.
 - ❖ Cutting boards and pans available.
- ❖ Preinstalled heavy-duty casters with brakes.
 - ❖ Electronic control system makes it easy to adjust temperature set point and defrost frequency.
 - ❖ Removable installation board makes it easy to access condenser coil for cleaning and service.
 - ❖ Option of different handles available.
 - ❖ These units use HYDRO-CARBON R290 refrigerant, which is environmentally friendly and more efficient than R134a/R404a refrigerant.

MODEL	DOORS	SHELVES	DIMENSIONS (WxDxH)	CAPACITY	HP	AMPS	VOLTAGE	PLUG TYPE
PS2-60	2	2	60 1/4 x 29 1/2 x 42 3/8 in 1529 x 750 x 1075 mm	15 cu.ft. 428 L	1/3	5.4	115/60/1	NEMA 5-15P
PS3	3	3	70 3/8 x 29 1/2 x 42 3/8 in 1787 x 750 x 1075 mm	15.5 cu.ft. 440 L	5/6	7.8	115/60/1	NEMA 5-15P

Mega Top Sandwich/Salad Prep Table

PAGE 1 OF 2



PS1M



PS2M-36



PS2M

- ❖ Stainless steel interior and exterior, aluminum back. Option of bright white aluminum interior available.
 - ❖ Refrigeration system keeps food at safe temperatures between 33°F and 40°F (0.5°C to 5°C).
 - ❖ Self-Closing doors with 90 degree stay-open feature. Locks and keys included.
 - ❖ Shelves: Adjustable heavy-duty PVC coated shelves.
 - ❖ Cutting boards and pans available.
- ❖ Preinstalled heavy-duty casters with brakes.
 - ❖ Electronic control system makes it easy to adjust temperature set point and defrost frequency.
 - ❖ Removable installation board makes it easy to access condenser coil for cleaning and service.
 - ❖ Option of different handles available.
 - ❖ These units use HYDRO-CARBON R290 refrigerant, which is environmentally friendly and more efficient than R134a/R404a refrigerant.

MODEL	DOORS	SHELVES	DIMENSIONS (WXDXH)	CAPACITY	HP	AMPS	VOLTAGE	PLUG TYPE
PS1M	1	1	27 1/2 x 34 x 45 7/8 in 698 x 864 x 1166 mm	5.7 cu.ft. 160 L	1/4+	3.9	115/60/1	NEMA 5-15P
PS2M-36	2	2	36 1/4 x 34 x 45 7/8 in 920 x 864 x 1166 mm	7.6 cu.ft. 213 L	1/4+	4.6	115/60/1	NEMA 5-15P
PS2M	2	2	46 7/8 x 34 x 45 7/8 in 1188 x 864 x 1166 mm	9.5 cu.ft. 268 L	1/3	5.4	115/60/1	NEMA 5-15P

Mega Top Sandwich/Salad Prep Table

PAGE 2 OF 2



PS2M-60



PS3M

- ❖ Stainless steel interior and exterior, aluminum back. Option of bright white aluminum interior available.
 - ❖ Refrigeration system keeps food at safe temperatures between 33°F and 40°F (0.5°C to 5°C).
 - ❖ Self-Closing doors with 90 degree stay-open feature. Locks and keys included.
 - ❖ Shelves: Adjustable heavy-duty PVC coated shelves.
 - ❖ Cutting boards and pans available.
- ❖ Preinstalled heavy-duty casters with brakes.
 - ❖ Electronic control system makes it easy to adjust temperature set point and defrost frequency.
 - ❖ Removable installation board makes it easy to access condenser coil for cleaning and service.
 - ❖ Option of different handles available.
 - ❖ These units use HYDRO-CARBON R290 refrigerant, which is environmentally friendly and more efficient than R134a/R404a refrigerant.

MODEL	DOORS	SHELVES	DIMENSIONS (WxDxH)	CAPACITY	HP	AMPS	VOLTAGE	PLUG TYPE
PS2M-60	2	2	60 1/4 x 34 x 45 7/8 in 1529 x 864 x 1166 mm	15 cu.ft. 428 L	1/3	6	115/60/1	NEMA 5-15P
PS3M	3	3	70 3/8 x 34 x 45 7/8 in 1787 x 864 x 1166 mm	15.5 cu.ft. 440 L	5/6	8.2	115/60/1	NEMA 5-15P



3 / 18

REFRIGERATED PIZZA PREP TABLE

Stainless steel pizza prep tables with refrigerated topping rails for consistent, high-volume pizza service.

PP1

PP2

PP3

Pizza Prep Table



- ❖ Stainless steel interior and exterior, aluminum back. Option of bright white aluminum interior available.
 - ❖ Refrigeration system keeps food at safe temperatures between 33°F and 40°F (0.5°C to 5°C).
 - ❖ Self-Closing doors with 90 degree stay-open feature. Locks and keys included.
 - ❖ Shelves: Adjustable heavy-duty PVC coated shelves.
 - ❖ Cutting boards and pans available.
- ❖ Preinstalled heavy-duty casters with brakes.
 - ❖ Electronic control system makes it easy to adjust temperature set point and defrost frequency.
 - ❖ Removable installation board makes it easy to access condenser coil for cleaning and service.
 - ❖ Option of different handles available.
 - ❖ These units use HYDRO-CARBON R290 refrigerant, which is environmentally friendly and more efficient than R134a/R404a refrigerant.

MODEL	DOORS	SHELVES	DIMENSIONS (WDXH)	CAPACITY	HP	AMPS	VOLTAGE	PLUG TYPE
PP1	1	1	49 7/8 x 31 1/2 x 42 7/8 in 1266 x 800 x 1088 mm	12 cu.ft. 340 L	1/4	4	115/60/1	NEMA 5-15P
PP2	2	2	70 7/8 x 31 1/2 x 42 7/8 in 1800 x 800 x 1088 mm	19 cu.ft. 547 L	1/3	5	115/60/1	NEMA 5-15P
PP3	3	3	91 7/8 x 31 1/2 x 42 7/8 in 2334 x 800 x 1088 mm	27 cu.ft. 754 L	1/2	7	115/60/1	NEMA 5-15P



4 / 18

CHEF BASE REFRIGERATOR

Low-profile refrigerated equipment stands that double as a cooking platform base, with heavy-duty pull-out drawers.

PCB36

PCB48

PCB52

PCB60

PCB72

PCB84

Chef Base Refrigerator



PCB36 / PCB48



PCB52 / PCB60



PCB72 / PCB84

- ✳ Stainless steel interior and exterior retains attractive finish longer. Matching aluminum finished back.
- ✳ Stainless steel top equipped with a marine edge enables the unit's top to contain drips and spills for easy cleanup.
- ✳ Refrigeration system keeps food at safe temperatures between 33°F and 40°F (0.5°C to 5°C).
- ✳ Preinstalled heavy-duty casters with brakes.
- ✳ Electronic control system makes it easy to adjust temperature set point and defrost frequency.
- ✳ Removable installation board makes it easy to access condenser coil for cleaning and service.
- ✳ Heavy-duty pull handles.
- ✳ These units use HYDRO-CARBON R290 refrigerant, which is environmentally friendly and more efficient than R134a/R404a refrigerant.

MODEL	DRAWERS	GN PANS	DIMENSIONS (WxDXH)	CAPACITY	HP	AMPS	VOLTAGE	PLUG TYPE
PCB36	2	2*1/1+6*1/6	36 3/8 x 32 1/8 x 25 7/8 in 924 x 816 x 645 mm	5.9 cu.ft. 167 L	1/6	2.52	115/60/1	NEMA 5-15P
PCB48	2	4*1/1 + 6*1/6	48 2/7 x 32 1/9 x 25 4/5 in 1228 x 816 x 655 mm	9.6 cu.ft. 270 L	1/6	2.1	115/60/1	NEMA 5-15P
PCB52	2	6*1/1	51 7/8 x 32 1/8 x 25 3/8 in 1318 x 816 x 645 mm	9.9 cu.ft. 280 L	1/6	3.48	115/60/1	NEMA 5-15P
PCB60	2	6*1/1 + 6*1/6	60 x 32 1/9 x 25 4/5 in 1524 x 816 x 655 mm	12.7 cu.ft. 360 L	1/6	2.9	115/60/1	NEMA 5-15P
PCB72	4	8*1/1	72 3/8 x 32 1/8 x 25 3/8 in 1839 x 816 x 645 mm	15 cu.ft. 425 L	1/5	4.68	115/60/1	NEMA 5-15P
PCB84	4	10*1/1	84 x 32 1/9 x 25 4/5 in 2134 x 816 x 655 mm	19 cu.ft. 538 L	1/5	3.9	115/60/1	NEMA 5-15P



5 / 18

UNDERCOUNTER COOLER / FREEZER

Compact undercounter refrigerators and freezers that fit under existing counters without sacrificing capacity.

PU27R

PU48R

PU60R

PU72R

PU27F

PU48F

PU60F

Undercounter Refrigerator



PU27R



PU48R / PU60R



PU72R

- ✱ Stainless steel interior and exterior, aluminum back. Option of bright white aluminum interior available.
 - ✱ Refrigeration system keeps food at safe temperatures between 33°F and 40°F (0.5°C to 5°C).
 - ✱ Self-Closing doors with 90 degree stay-open feature. Locks and keys included.
 - ✱ Shelves: Adjustable heavy-duty PVC coated shelves.
 - ✱ Option of Backsplashes available.
- ✱ Preinstalled heavy-duty casters with brakes.
 - ✱ Electronic control system makes it easy to adjust temperature set point and defrost frequency.
 - ✱ Removable installation board makes it easy to access condenser coil for cleaning and service.
 - ✱ Option of different handles available.
 - ✱ These units use HYDRO-CARBON R290 refrigerant, which is environmentally friendly and more efficient than R134a/R404a refrigerant.

MODEL	DOORS	SHELVES	DIMENSIONS (WDXH)	CAPACITY	HP	AMPS	VOLTAGE	PLUG TYPE
PU27R	1	1	27 x 29 1/2 x 35 1/4 in 685 x 750 x 895 mm	6 cu.ft. 177 L	1/7	1.8	115/60/1	NEMA 5-15P
PU48R	2	2	47 1/4 x 29 1/2 x 35 1/4 in 1200 x 750 x 895 mm	12 cu.ft. 338 L	1/5	2.4	115/60/1	NEMA 5-15P
PU60R	2	2	60 1/4 x 29 1/2 x 35 1/4 in 1529 x 750 x 895 mm	17 cu.ft. 490 L	1/5	2.6	115/60/1	NEMA 5-15P
PU72R	3	3	71 1/2 x 29 1/2 x 35 1/4 in 1815 x 750 x 895 mm	21 cu.ft. 588 L	1/5	2.7	115/60/1	NEMA 5-15P

Undercounter Freezer



PU27F



PU48F



PU60F

- ❖ Stainless steel interior and exterior, aluminum back. Option of bright white aluminum interior available.
 - ❖ Refrigeration system keeps food at safe temperatures between -8°F and 0°F (-22°C to -18°C).
 - ❖ Self-Closing doors with 90 degree stay-open feature. Locks and keys included.
 - ❖ Shelves: Adjustable heavy-duty PVC coated shelves.
 - ❖ Option of Backsplashes available.
- ❖ Preinstalled heavy-duty casters with brakes.
 - ❖ Electronic control system makes it easy to adjust temperature set point and defrost frequency.
 - ❖ Removable installation board makes it easy to access condenser coil for cleaning and service.
 - ❖ Option of different handles available.
 - ❖ These units use HYDRO-CARBON R290 refrigerant, which is environmentally friendly and more efficient than R134a/R404a refrigerant.

MODEL	DOORS	SHELVES	DIMENSIONS (WxDxH)	CAPACITY	HP	AMPS	VOLTAGE	PLUG TYPE
PU27F	1	1	27 x 29 1/2 x 35 1/4 in 685 x 750 x 895 mm	6 cu.ft. 177 L	1/5	3.6	115/60/1	NEMA 5-15P
PU48F	2	2	47 1/4 x 29 1/2 x 35 1/4 in 1200 x 750 x 895 mm	12 cu.ft. 338 L	1/4+	4.5	115/60/1	NEMA 5-15P
PU60F	2	2	60 1/4 x 29 1/2 x 35 1/4 in 1529 x 750 x 895 mm	17 cu.ft. 490 L	2/3	4.5	115/60/1	NEMA 5-15P



6 / 18

WORK TOP COOLER / FREEZER

Worktop refrigerators and freezers with a durable stainless steel work surface built directly on top of refrigerated storage.

PWT27R

PWT48R

PWT60R

PWT72R

PWT27F

PWT48F

PWT60F

Worktop Refrigerator



PWT27R



PWT48R / PWT60R



PWT72R

- ✳ Stainless steel interior and exterior, aluminum back. Option of bright white aluminum interior available.
- ✳ Refrigeration system keeps food at safe temperatures between 33°F and 40°F (0.5°C to 5°C).
- ✳ Self-Closing doors with 90 degree stay-open feature. Locks and keys included.
- ✳ Shelves: Adjustable heavy-duty PVC coated shelves.
- ✳ Preinstalled heavy-duty casters with brakes.

- ✳ Electronic control system makes it easy to adjust temperature set point and defrost frequency.
- ✳ Removable installation board makes it easy to access condenser coil for cleaning and service.
- ✳ Option of different handles available.
- ✳ These units use HYDRO-CARBON R290 refrigerant, which is environmentally friendly and more efficient than R134a/R404a refrigerant.

MODEL	DOORS	SHELVES	DIMENSIONS (WXDXH)	CAPACITY	HP	AMPS	VOLTAGE	PLUG TYPE
PWT27R	1	1	27 x 29 1/2 x 38 3/4 in 685 x 750 x 984 mm	6 cu.ft. 177 L	1/7	1.8	115/60/1	NEMA 5-15P
PWT48R	2	2	47 1/4 x 29 1/2 x 38 3/4 in 1200 x 750 x 984 mm	12 cu.ft. 338 L	1/5	2.4	115/60/1	NEMA 5-15P
PWT60R	2	2	60 1/4 x 29 1/2 x 38 3/4 in 1529 x 750 x 984 mm	17 cu.ft. 490 L	1/5	2.6	115/60/1	NEMA 5-15P
PWT72R	3	3	71 1/2 x 29 1/2 x 38 3/4 in 1815 x 750 x 984 mm	21 cu.ft. 588 L	1/5	2.7	115/60/1	NEMA 5-15P

Worktop Freezer



- ✱ Stainless steel interior and exterior, aluminum back. Option of bright white aluminum interior available.
- ✱ Refrigeration system keeps food at safe temperatures between -8°F and 0°F (-22°C to -18°C).
- ✱ Self-Closing doors with 90 degree stay-open feature. Locks and keys included.
- ✱ Shelves: Adjustable heavy-duty PVC coated shelves.
- ✱ Preinstalled heavy-duty casters with brakes.
- ✱ Electronic control system makes it easy to adjust temperature set point and defrost frequency.
- ✱ Removable installation board makes it easy to access condenser coil for cleaning and service.
- ✱ Option of different handles available.
- ✱ These units use HYDRO-CARBON R290 refrigerant, which is environmentally friendly and more efficient than R134a/R404a refrigerant.

MODEL	DOORS	SHELVES	DIMENSIONS (WxDxH)	CAPACITY	HP	AMPS	VOLTAGE	PLUG TYPE
PWT27F	1	1	27 x 29 1/2 x 38 3/4 in 685 x 750 x 984 mm	6 cu.ft. 177 L	1/5	3.6	115/60/1	NEMA 5-15P
PWT48F	2	2	47 1/4 x 29 1/2 x 38 3/4 in 1200 x 750 x 984 mm	12 cu.ft. 338 L	1/4+	4.5	115/60/1	NEMA 5-15P
PWT60F	2	2	60 1/4 x 29 1/2 x 38 3/4 in 1529 x 750 x 984 mm	17 cu.ft. 490 L	2/3	4.5	115/60/1	NEMA 5-15P



7 / 18

BACKBAR COOLER / BEER DISPENSER

Back bar refrigeration and direct draw beer dispensers finished in durable black vinyl, sized for 24 in. and 27 in. depths.

PBB24-48G

PBB24-60G

PBB24-72G

PBB24-48S

PBB24-60S

PBB24-72S

PDD24-48

PDD24-60

PDD24-72

PDD1

PDD2

PDD3

PDD4

PBB1G

PBB2G

PBB3G

PBB4G

PBB1S

PBB2S

PBB3S

PBB4S

Back Bar Cooler

24" DEPTH GLASS DOOR



- ✱ Durable stainless steel top, interior walls, floor and ceiling.
 - ✱ Exterior construction is attractive corrosion resistant vinyl on steel in black finish.
 - ✱ Refrigeration system keeps the drinks at safe temperatures between 33°F and 40°F (0.5°C to 5°C).
 - ✱ Electronic control system makes it easy to adjust temperature set point and defrost frequency.
 - ✱ Shelves: Adjustable heavy-duty PVC coated shelves.
 - ✱ Option of stainless steel exterior available.
- ✱ Preinstalled heavy-duty casters with brakes.
 - ✱ Option of leveling feet available.
 - ✱ Self-Closing doors with locks.
 - ✱ LED interior lighting.
 - ✱ Removable installation board makes it easy to access condenser coil for cleaning and service.
 - ✱ These units use HYDRO-CARBON R290 refrigerant, which is environmentally friendly and more efficient than R134a/R404a refrigerant.

MODEL	DOORS	SHELVES	DIMENSIONS (WxDxH)	CAPACITY	HP	AMPS	VOLTAGE	PLUG TYPE
PBB24-48G	2	4	48 7/8 x 24 3/8 x 35 5/8 in 1240 x 620 x 905 mm	11.2 cu.ft. 318 L	3/7	3.5	115/60/1	NEMA 5-15P
PBB24-60G	2	4	60 3/4 x 24 3/8 x 35 5/8 in 1544 x 620 x 905 mm	14.8 cu.ft. 420 L	3/7	3.5	115/60/1	NEMA 5-15P
PBB24-72G	3	6	72 3/4 x 24 3/8 x 35 5/8 in 1848 x 620 x 905 mm	18.5 cu.ft. 525 L	3/7	3.5	115/60/1	NEMA 5-15P

Back Bar Cooler

24" DEPTH SOLID DOOR



PBB24-48S



PBB24-60S



PBB24-72S

- ✱ Durable stainless steel top, interior walls, floor and ceiling.
 - ✱ Exterior construction is attractive corrosion resistant vinyl on steel in black finish.
 - ✱ Refrigeration system keeps the drinks at safe temperatures between 33°F and 40°F (0.5°C to 5°C).
 - ✱ Electronic control system makes it easy to adjust temperature set point and defrost frequency.
 - ✱ Shelves: Adjustable heavy-duty PVC coated shelves.
 - ✱ Option of stainless steel exterior available.
- ✱ Preinstalled heavy-duty casters with brakes.
 - ✱ Option of leveling feet available.
 - ✱ Self-Closing doors with locks.
 - ✱ LED interior lighting.
 - ✱ Removable installation board makes it easy to access condenser coil for cleaning and service.
 - ✱ These units use HYDRO-CARBON R290 refrigerant, which is environmentally friendly and more efficient than R134a/R404a refrigerant.

MODEL	DOORS	SHELVES	DIMENSIONS (WXDXH)	CAPACITY	HP	AMPS	VOLTAGE	PLUG TYPE
PBB24-48S	2	4	48 7/8 x 24 3/8 x 35 5/8 in 1240 x 620 x 905 mm	11.2 cu.ft. 318 L	3/7	3.5	115/60/1	NEMA 5-15P
PBB24-60S	2	4	60 3/4 x 24 3/8 x 35 5/8 in 1544 x 620 x 905 mm	14.8 cu.ft. 420 L	3/7	3.5	115/60/1	NEMA 5-15P
PBB24-72S	3	6	72 3/4 x 24 3/8 x 35 5/8 in 1848 x 620 x 905 mm	18.5 cu.ft. 525 L	3/7	3.5	115/60/1	NEMA 5-15P

Direct Draw Beer Dispenser

24" DEPTH



- ✱ Durable stainless steel top, interior walls, floor and ceiling.
 - ✱ Exterior construction is attractive corrosion resistant vinyl on steel in black finish.
 - ✱ Refrigeration system keeps the drinks at safe temperatures between 33°F and 40°F (0.5°C to 5°C).
 - ✱ Electronic control system makes it easy to adjust temperature set point and defrost frequency.
 - ✱ Shelves: Adjustable heavy-duty PVC coated shelves.
 - ✱ Option of stainless steel exterior available.
- ✱ Preinstalled heavy-duty casters with brakes.
 - ✱ Option of leveling feet available.
 - ✱ Self-Closing doors with locks.
 - ✱ LED interior lighting.
 - ✱ Removable installation board makes it easy to access condenser coil for cleaning and service.
 - ✱ These units use HYDRO-CARBON R290 refrigerant, which is environmentally friendly and more efficient than R134a/R404a refrigerant.

MODEL	DOORS	SHELVES	DIMENSIONS (WXDXH)	CAPACITY (BARRELS)	HP	AMPS	VOLTAGE	PLUG TYPE
PDD24-48	2	4	48 7/8 x 24 3/8 x 35 5/8 in 1240 x 620 x 905 mm	2*1/2	3/7	3.5	115/60/1	NEMA 5-15P
PDD24-60	2	4	60 3/4 x 24 3/8 x 35 5/8 in 1544 x 620 x 905 mm	2*1/2	3/7	3.5	115/60/1	NEMA 5-15P
PDD24-72	3	6	72 3/4 x 24 3/8 x 35 5/8 in 1848 x 620 x 905 mm	3*1/2	3/7	3.5	115/60/1	NEMA 5-15P

* Height does not include 15.8" (402mm) for draft arm.

Direct Draw Beer Dispenser

27" DEPTH



- ✱ Durable stainless steel top, interior walls, floor and ceiling.
 - ✱ Exterior construction is attractive corrosion resistant vinyl on steel in black finish.
 - ✱ Refrigeration system keeps the drinks at safe temperatures between 33°F and 40°F (0.5°C to 5°C).
 - ✱ Electronic control system makes it easy to adjust temperature set point and defrost frequency.
 - ✱ Shelves: Adjustable heavy-duty PVC coated shelves.
 - ✱ Option of stainless steel exterior available.
- ✱ Preinstalled heavy-duty casters with brakes.
 - ✱ Option of leveling feet available.
 - ✱ Self-Closing doors with locks.
 - ✱ LED interior lighting.
 - ✱ Removable installation board makes it easy to access condenser coil for cleaning and service.
 - ✱ These units use HYDRO-CARBON R290 refrigerant, which is environmentally friendly and more efficient than R134a/R404a refrigerant.

MODEL	DOORS	SHELVES	DIMENSIONS (WXDXH)	CAPACITY (BARRELS)	HP	AMPS	VOLTAGE	PLUG TYPE
PDD1	1	1	23 1/2 x 30 3/8 x 38 3/4 in 596 x 772 x 983 mm	1*1/2	1/4	1.92	115/60/1	NEMA 5-15P
PDD2	2	4	58 7/8 x 27 3/4 x 35 5/8 in 1495 x 705 x 905 mm	2*1/2	3/7	3.5	115/60/1	NEMA 5-15P
PDD3	2	4	69 1/8 x 27 3/4 x 35 5/8 in 1755 x 705 x 905 mm	3*1/2	3/7	3.5	115/60/1	NEMA 5-15P
PDD4	3	6	90 3/8 x 27 3/4 x 35 5/8 in 2295 x 705 x 905 mm	4*1/2	1/2	4.1	115/60/1	NEMA 5-15P

* Height does not include 15.8" (402mm) for draft arm.

Back Bar Cooler

27" DEPTH GLASS DOOR



- ✳ Durable stainless steel top, interior walls, floor and ceiling.
- ✳ Exterior construction is attractive corrosion resistant vinyl on steel in black finish.
- ✳ Refrigeration system keeps the drinks at safe temperatures between 33°F and 40°F (0.5°C to 5°C).
- ✳ Electronic control system makes it easy to adjust temperature set point and defrost frequency.
- ✳ Shelves: Adjustable heavy-duty PVC coated shelves.
- ✳ Option of stainless steel exterior available.
- ✳ Preinstalled heavy-duty casters with brakes.
- ✳ Option of leveling feet available.
- ✳ Self-Closing doors with locks.
- ✳ LED interior lighting.
- ✳ Removable installation board makes it easy to access condenser coil for cleaning and service.
- ✳ These units use HYDRO-CARBON R290 refrigerant, which is environmentally friendly and more efficient than R134a/R404a refrigerant.

MODEL	DOORS	SHELVES	DIMENSIONS (WxDxH)	CAPACITY	HP	AMPS	VOLTAGE	PLUG TYPE
PBB1G	1	1	23 1/2 x 30 3/8 x 38 3/4 in 596 x 772 x 983 mm	6.5 cu.ft. 186 L	1/4	1.92	115/60/1	NEMA 5-15P
PBB2G	2	4	58 7/8 x 27 3/4 x 35 5/8 in 1495 x 705 x 905 mm	19 cu.ft. 540 L	3/7	3.5	115/60/1	NEMA 5-15P
PBB3G	2	4	69 1/8 x 27 3/4 x 35 5/8 in 1755 x 705 x 905 mm	23.3 cu.ft. 660 L	3/7	3.5	115/60/1	NEMA 5-15P
PBB4G	3	6	90 3/8 x 27 3/4 x 35 5/8 in 2295 x 705 x 905 mm	32 cu.ft. 910 L	1/2	4.1	115/60/1	NEMA 5-15P

Back Bar Cooler

27" DEPTH SOLID DOOR



PBB1S

PBB2S

PBB3S

PBB4S

- ✱ Durable stainless steel top, interior walls, floor and ceiling.
 - ✱ Exterior construction is attractive corrosion resistant vinyl on steel in black finish.
 - ✱ Refrigeration system keeps the drinks at safe temperatures between 33°F and 40°F (0.5°C to 5°C).
 - ✱ Electronic control system makes it easy to adjust temperature set point and defrost frequency.
 - ✱ Shelves: Adjustable heavy-duty PVC coated shelves.
 - ✱ Option of stainless steel exterior available.
- ✱ Preinstalled heavy-duty casters with brakes.
 - ✱ Option of leveling feet available.
 - ✱ Self-Closing doors with locks.
 - ✱ LED interior lighting.
 - ✱ Removable installation board makes it easy to access condenser coil for cleaning and service.
 - ✱ These units use HYDRO-CARBON R290 refrigerant, which is environmentally friendly and more efficient than R134a/R404a refrigerant.

MODEL	DOORS	SHELVES	DIMENSIONS (WXDXH)	CAPACITY	HP	AMPS	VOLTAGE	PLUG TYPE
PBB1S	1	1	23 1/2 x 30 3/8 x 38 3/4 in 596 x 772 x 983 mm	6.5 cu.ft. 186 L	1/4	1.92	115/60/1	NEMA 5-15P
PBB2S	2	4	58 7/8 x 27 3/4 x 35 5/8 in 1495 x 705 x 905 mm	19 cu.ft. 540 L	3/7	3.5	115/60/1	NEMA 5-15P
PBB3S	2	4	69 1/8 x 27 3/4 x 35 5/8 in 1755 x 705 x 905 mm	23.3 cu.ft. 660 L	3/7	3.5	115/60/1	NEMA 5-15P
PBB4S	3	6	90 3/8 x 27 3/4 x 35 5/8 in 2295 x 705 x 905 mm	32 cu.ft. 910 L	1/2	4.1	115/60/1	NEMA 5-15P



8 / 18

HORIZONTAL BOTTLE COOLER

Horizontal bottle coolers with sliding lids and adjustable dividers, built for high-volume beverage storage behind the bar.

PBC26

PBC36

PBC50

PBC65

PBC95

Horizontal Bottle Cooler



- ✱ Durable stainless steel top, interior walls, floor and ceiling.
- ✱ Exterior construction is attractive corrosion resistant vinyl on steel in black finish.
- ✱ Refrigeration system keeps the drinks at safe temperatures between 33°F and 40°F (0.5°C to 4.5°C).
- ✱ Removable bottle cap opener and cap catcher included.
- ✱ Option of stainless steel exterior available.
- ✱ Electronic control system makes it easy to adjust temperature set point and defrost frequency.
- ✱ Removable installation board makes it easy to access condenser coil for cleaning and service.
- ✱ Adjustable coated-steel dividers included.
- ✱ These units use HYDRO-CARBON R290 refrigerant, which is environmentally friendly and more efficient than R134a/R404a refrigerant.

MODEL	LIDS	DIMENSIONS (WXDXH)	CAPACITY (12OZ BOTTLES)	CAPACITY (12OZ CANS)	HP	AMPS	VOLTAGE	PLUG TYPE
PBC26	1	26 3/8 x 28 3/8 x 34 1/4 in 670 x 713 x 869 mm	4.5	6	1/4	2.4	115/60/1	NEMA 5-15P
PBC36	1	36 x 28 x 34 1/4 in 915 x 713 x 869 mm	11	14.5	1/4	2.4	115/60/1	NEMA 5-15P
PBC50	2	49 1/2 x 26 5/8 x 34 1/4 in 1257 x 713 x 869 mm	16.5	24	1/4	2.5	115/60/1	NEMA 5-15P
PBC65	2	64 1/2 x 26 5/8 x 34 1/4 in 1638 x 713 x 869 mm	22	32	1/3	2.5	115/60/1	NEMA 5-15P
PBC95	3	95 1/5 x 26 5/8 x 34 1/4 in 2418 x 713 x 869 mm	37.5	55	1/2	3.3	115/60/1	NEMA 5-15P



9 / 18

HORIZONTAL BEER FROSTER

Horizontal beer frosters that chill bottles and cans down to near-freezing for the coldest possible pour, built on the same rugged sliding-lid, high-volume design as our bottle coolers.

PBF26-SZ

PBF36-SZ

PBF50-SZ

PBF65-SZ

PBF80-SZ

PBF95-SZ

Horizontal Beer Froster



PBF26-SZ



PBF36-SZ



PBF50-SZ / PBF65-SZ



PBF80-SZ / PBF95-SZ

- ✳ Durable stainless steel top, interior walls, floor and ceiling.
- ✳ Exterior construction is attractive corrosion resistant vinyl on steel in black finish.
- ✳ Refrigeration system keeps beer at frosty temperatures between 18°F and 33°F (-8°C to +1°C) — colder than a standard bottle cooler, for the perfect frosty pour.
- ✳ These units use HYDRO-CARBON R290 refrigerant, which is environmentally friendly and more efficient than R134a/R404a refrigerant.
- ✳ Adjustable coated-steel dividers included.
- ✳ Electronic control system makes it easy to adjust temperature set point and defrost frequency.
- ✳ Removable installation board makes it easy to access condenser coil for cleaning and service.
- ✳ Option of stainless steel exterior available.

MODEL	LIDS	DIMENSIONS (WXDXH)	CAPACITY (12OZ BOTTLES)	CAPACITY (12OZ CANS)	HP	AMPS	VOLTAGE	PLUG TYPE
PBF26-SZ	1	26 3/8 x 28 3/8 x 34 1/4 in 670 x 713 x 869 mm	104	156	1/4	2.4	115/60/1	NEMA 5-15P
PBF36-SZ	1	36 x 28 x 34 1/4 in 915 x 713 x 869 mm	130	196	1/4	2.4	115/60/1	NEMA 5-15P
PBF50-SZ	2	49 1/2 x 26 5/8 x 34 1/4 in 1257 x 713 x 869 mm	208	308	1/4	2.5	115/60/1	NEMA 5-15P
PBF65-SZ	2	64 1/2 x 26 5/8 x 34 1/4 in 1638 x 713 x 869 mm	288	432	1/3	2.5	115/60/1	NEMA 5-15P
PBF80-SZ	3	79 1/2 x 26 5/8 x 34 1/4 in 2020 x 713 x 869 mm	368	556	1/2	3.3	115/60/1	NEMA 5-15P
PBF95-SZ	3	95 1/5 x 26 5/8 x 34 1/4 in 2418 x 713 x 869 mm	456	688	1/2	3.3	115/60/1	NEMA 5-15P



10 / 18

GLASS FROSTER

Glass and plate frosters that chill glassware and dinnerware well below freezing for the perfect frosted serve.

PGF26

PGF36

PGF50

Glass Froster



PGF26



PGF36



PGF50

- ✱ Durable stainless steel top, interior walls, floor and ceiling.
 - ✱ Exterior construction is attractive corrosion resistant vinyl on steel in black finish.
 - ✱ Refrigeration system keeps the glasses/plates at safe temperatures between -5°F and 2°F.
 - ✱ Adjustable coated-steel dividers included.
 - ✱ Option of stainless steel exterior available.
- ✱ Electronic control system makes it easy to adjust temperature set point and defrost frequency.
 - ✱ Removable installation board makes it easy to access condenser coil for cleaning and service.
 - ✱ These units use HYDRO-CARBON R290 refrigerant, which is environmentally friendly and more efficient than R134a/R404a refrigerant.

MODEL	LIDS	DIMENSIONS (WXDXH)	CAPACITY (8" MUGS)	CAPACITY (10OZ STEINS)	HP	AMPS	VOLTAGE	PLUG TYPE
PGF26	1	26 3/8 x 26 5/8 x 34 1/4 in 670 x 677 x 869 mm	90	85	1/3	2.4	115/60/1	NEMA 5-15P
PGF36	2	36 x 26 5/8 x 34 1/4 in 915 x 677 x 869 mm	165	155	1/2	3.3	115/60/1	NEMA 5-15P
PGF50	2	49 1/2 x 26 5/8 x 34 1/4 in 1257 x 677 x 869 mm	250	240	1/2	5.3	115/60/1	NEMA 5-15P

Voltage 230-240/50/1 available. Plug type varies by country.



11 / 18

REFRIGERATED DELI CASE

Curved-glass and double-duty deli display cases that keep meats and prepared foods merchandised at safe temperatures.

PDC36-SS

PDC47-SS

PDC64-SS

PDC82-SS

PDCDT50

PDCDT71

PDCDT84

Refrigerated Deli Case



PDC36-SS / PDC47-SS



PDC64-SS / PDC82-SS

- ✳ Interior: Aluminum liner with stainless steel floor.
- ✳ Exterior: Black or white coated steel. Stainless steel available.
- ✳ Attractive curved glass and sliding glass doors.
- ✳ Rounded corner design inside of the cabinet makes it easy to clean the inside storage room.
- ✳ Refrigeration system keeps the meats and deli products at safe temperatures between 32°F and 43°F (0°C to 6°C).
- ✳ Preinstalled heavy-duty casters with brakes.

- ✳ Electronic control system makes it easy to adjust temperature set point and defrost frequency.
- ✳ Removable installation board makes it easy to access condenser coil for cleaning and service.
- ✳ Shelves: Adjustable heavy-duty PVC coated shelves.
- ✳ LED interior lighting.
- ✳ These units use HYDRO-CARBON R290 refrigerant, which is environmentally friendly and more efficient than R134a/R404a refrigerant.

MODEL	DOORS	SHELVES	DIMENSIONS (WxDxH)	CAPACITY	HP	AMPS	VOLTAGE	PLUG TYPE
PDC36-SS	2	6	36 x 32 1/2 x 42 7/8 in 920 x 825 x 1089 mm	12 cu.ft. 330 L	1/3	4.68	115/60/1	NEMA 5-15P
PDC47-SS	2	6	48 x 32 1/2 x 42 7/8 in 1200 x 825 x 1089 mm	18 cu.ft. 508 L	1/4+	3.12	115/60/1	NEMA 5-15P
PDC64-SS	3	9	64 x 32 1/2 x 42 7/8 in 1630 x 825 x 1089 mm	22 cu.ft. 620 L	3/5	7.14	115/60/1	NEMA 5-15P
PDC82-SS	3	9	82 x 32 1/2 x 42 7/8 in 2082 x 825 x 1089 mm	32 cu.ft. 903 L	3/4	7.08	115/60/1	NEMA 5-15P

Double Duty Refrigerated Deli Case



- ❖ Double duty deli cases offer two refrigerated compartments. One for display to provide an area for ready to serve deli products under the lighting and a second lower compartment for storage.
- ❖ Refrigeration system holds 38°F to 40°F (3.3°C to 4.4°C). Gravity coil refrigeration system provides high humidity environment for exceptional preservation of meats and deli products.
- ❖ CONFORMS TO NSF/ANSI STD. 7
- ❖ "Low-E", double pane thermal glass front display and rear doors provide maximum insulation value for greater efficiency and energy savings.
- ❖ Exterior: three options, stainless steel, white, and black.
- ❖ Interior: attractive, NSF approved, white aluminum liner. Stainless steel floor with coved corners.
- ❖ Automatic defrost electronically controlled
- ❖ LED lighting

MODEL	DOORS	SHELVES	DIMENSIONS (WXDXH)	HP	VOLTAGE	AMPS	PLUG TYPE
PDCDT50	2	2	50 x 35 1/2 x 57 in 1270 x 902 x 1448 mm	4/5	115/60/1	5.0	5-15P
PDCDT71	2	2	71 x 35 1/2 x 57 in 1805 x 902 x 1448 mm	1	115/60/1	7.7	5-15P
PDCDT84	3	2	84 x 35 1/2 x 57 in 2135 x 902 x 1448 mm	1	115/60/1	10.2	5-15P



1 2 / 1 8

MERCHANDISER REFRIGERATOR

Glass door merchandiser refrigerators in countertop, swing-door and sliding-door formats for grab-and-go retail display.

PMR24-1A

PMR24-1B

PMR21-1

PMR26-1

PMR25-1

PMR28-1

PMR53-2Y

PMR48-2

PMR53-2

PMR78-3

PMR29-1

PMR54-2

PMR79-3

Countertop Merchandiser



PMR24-1A



PMR24-1B

- ✧ Exterior: Coated steel. Black or white or S/S finish available.
 - ✧ Interior: Attractive aluminum liner with stainless steel floor.
 - ✧ Refrigeration system maintains temperatures between 33°F and 41°F (0.5°C to 4.5°C).
 - ✧ Swing glass door.
 - ✧ Shelves: Adjustable heavy-duty PVC coated shelves.
- ✧ LED lighting.
 - ✧ Electronic control system makes it easy to adjust temperature set point and defrost frequency.
 - ✧ R290 natural refrigerant.
 - ✧ Removable installation board makes it easy to access condenser coil for cleaning and service.

MODEL	DOORS	SHELVES	DIMENSIONS (WxDxH)	CAPACITY	HP	AMPS	VOLTAGE	PLUG TYPE
PMR24-1A	1	2	24 2/5 x 25 1/5 x 33 1/4 in 620 x 640 x 845 mm	5 cu.ft. 140 L	1/5	1.8	115/60/1	NEMA 5-15P
PMR24-1B	1	3	24 2/5 x 25 1/5 x 38 3/5 in 620 x 640 x 980 mm	6.4 cu.ft. 180 L	1/5	2	115/60/1	NEMA 5-15P

Merchandising Swing Glass Door Refrigerator



PMR21-1



PMR26-1 / PMR25-1



PMR28-1

- ✧ Exterior: Coated steel. Black or white finish available.
- ✧ Interior: Attractive aluminum liner with stainless steel floor.
- ✧ Refrigeration system maintains temperatures between 33°F and 40°F (0.5°C to 5°C).
- ✧ Self-Closing double pane glass door with positive seal.
- ✧ Shelves: Adjustable heavy-duty PVC coated shelves.
- ✧ Leveling feet or casters are available.

- ✧ LED lighting.
- ✧ Electronic control system makes it easy to adjust temperature set point and defrost frequency.
- ✧ Removable installation board makes it easy to access condenser coil for cleaning and service.
- ✧ These units use HYDRO-CARBON R290 refrigerant, which is environmentally friendly and more efficient than R134a/R404a refrigerant.

MODEL	DOORS	SHELVES	DIMENSIONS (WxDxH)	CAPACITY	HP	AMPS	VOLTAGE	PLUG TYPE
PMR21-1	1	4	21 5/8 x 21 5/8 x 63 in 550 x 550 x 1600 mm	9.1 cu.ft. 258 L	1/5	2.5	115/60/1	NEMA 5-15P
PMR26-1	1	4	26 x 25 3/5 x 80 3/8 in 660 x 650 x 2040 mm	13 cu.ft. 368 L	1/5	3.12	115/60/1	NEMA 5-15P
PMR25-1	1	4	25 3/5 x 22 4/5 x 79 3/8 in 650 x 580 x 2015 mm	14 cu.ft. 398 L	1/5	2.5	115/60/1	NEMA 5-15P
PMR28-1	1	4	28 3/8 x 31 7/8 x 79 3/8 in 720 x 810 x 2015 mm	23 cu.ft. 648 L	1/5	3	115/60/1	NEMA 5-15P

Merchandising Sliding Glass Door Refrigerator



PMR53-2Y



PMR53-2Y

- ✱ Exterior: Coated steel. Black or white finish available.
 - ✱ Interior: Attractive aluminum liner with stainless steel floor.
 - ✱ Refrigeration system maintains temperatures between 33°F and 40°F (0.5°C to 5°C).
 - ✱ Self-Closing double pane glass door with positive seal.
 - ✱ Shelves: Adjustable heavy-duty PVC coated shelves.
 - ✱ Leveling feet or casters are available.
- ✱ LED lighting.
 - ✱ Electronic control system makes it easy to adjust temperature set point and defrost frequency.
 - ✱ Removable installation board makes it easy to access condenser coil for cleaning and service.
 - ✱ These units use HYDRO-CARBON R290 refrigerant, which is environmentally friendly and more efficient than R134a/R404a refrigerant.

MODEL	DOORS	SHELVES	DIMENSIONS (WxDxH)	CAPACITY	HP	AMPS	VOLTAGE	PLUG TYPE
PMR53-2Y (Black / White)		8	53 1/8 x 31 7/8 x 79 3/8 in 1350 x 810 x 2015 mm	45 cu.ft. 1270 L	1/4+	6	115/60/1	NEMA 5-15P

Merchandising Swing Glass Door Refrigerator

LARGE



PMR48-2



PMR53-2



PMR78-3

- ❖ Exterior: Coated steel. Black or white finish available.
 - ❖ Interior: Attractive aluminum liner with stainless steel floor.
 - ❖ Refrigeration system maintains temperatures between 33°F and 40°F (0.5°C to 5°C).
 - ❖ Self-Closing double pane glass door with positive seal.
 - ❖ Shelves: Adjustable heavy-duty PVC coated shelves.
 - ❖ Leveling feet or casters are available.
- ❖ LED lighting.
 - ❖ Electronic control system makes it easy to adjust temperature set point and defrost frequency.
 - ❖ Removable installation board makes it easy to access condenser coil for cleaning and service.
 - ❖ These units use HYDRO-CARBON R290 refrigerant, which is environmentally friendly and more efficient than R134a/R404a refrigerant.

MODEL	DOORS	SHELVES	DIMENSIONS (WDXH)	CAPACITY	HP	AMPS	VOLTAGE	PLUG TYPE
PMR48-2	2	8	48 x 25 3/5 x 80 3/8 in 1220 x 650 x 2040 mm	29 cu.ft. 830 L	1/4+	4.8	115/60/1	NEMA 5-15P
PMR53-2 (Black / White)		8	53 1/8 x 31 7/8 x 79 3/8 in 1350 x 810 x 2015 mm	45 cu.ft. 1270 L	1/4+	6	115/60/1	NEMA 5-15P
PMR78-3	3	12	78 3/8 x 30 x 80 3/8 in 1988 x 760 x 2040 mm	53 cu.ft. 1500 L	3/4	8.4	115/60/1	NEMA 5-15P

Swing Door Refrigerator with Hydrocarbon Refrigerant



- ❖ High capacity, factory balanced refrigeration system that maintains cabinet temperatures of 33°F to 41°F (0.5°C to 5°C) for the best food, beverage and soft drinks preservation in extreme conditions.
 - ❖ Rounded corner design inside of the cabinet makes it easy to clean the inside storage room.
 - ❖ LED lighting.
 - ❖ Double pane glass door. Self closing. Positive seal, torsion type closure system.
- ❖ Exterior - Coated steel. Interior - attractive, aluminum liner with stainless steel floor.
 - ❖ Foamed with polyurethane, high-density cell insulation that has zero ozone depletion potential.
 - ❖ Adjustable temperature set point and defrost frequency. Error codes to diagnose service issues.
 - ❖ Adjustable, heavy duty PVC coated shelves.
 - ❖ Exterior Optional: white or stainless steel finish available.

MODEL	DOORS	SHELVES	DIMENSIONS (WXDXH)	CAPACITY	HP	AMPS	VOLTAGE	PLUG TYPE
PMR29-1	1	4	29 1/2 x 26 2/5 x 82 1/5 in 750 x 670 x 2088 mm	16.3 cu.ft. 462 L	1/4	3.4	115V/60Hz	NEMA 5-15P
PMR54-2	2	8	53 8/9 x 27 8/9 x 82 1/5 in 1370 x 710 x 2088 mm	35.5 cu.ft. 1006 L	1/3	4.5	115V/60Hz	NEMA 5-15P
PMR79-3	3	12	78 5/7 x 30 5/7 x 84 1/5 in 2000 x 780 x 2088 mm	59.5 cu.ft. 1686 L	3/7	6.9	115V/60Hz	NEMA 5-15P



13 / 18

MERCHANDISER FREEZER

Glass door merchandiser freezers built to the same G-Series look as our merchandiser refrigerators, for frozen grab-and-go retail.

PMF26-1

PMF27-1

PMF31-1

PMF49-2

PMF53-2

PMF79-3

Merchandising Swing Glass Door Freezer

PAGE 1 OF 2



PMF26-1



PMF27-1



PMF31-1

- ❖ Exterior: Coated steel. Black or white finish available.
 - ❖ Interior: Attractive aluminum liner with stainless steel floor.
 - ❖ Refrigeration system maintains temperatures between -8°F and 0°F (-23°C to -18°C).
 - ❖ Self-Closing double pane glass door with positive seal.
 - ❖ Shelves: Adjustable heavy-duty PVC coated shelves.
 - ❖ Leveling feet or casters are available.
- ❖ LED lighting.
 - ❖ Electronic control system makes it easy to adjust temperature set point and defrost frequency.
 - ❖ Removable installation board makes it easy to access condenser coil for cleaning and service.
 - ❖ These units use HYDRO-CARBON R290 refrigerant, which is environmentally friendly and more efficient than R134a/R404a refrigerant.

MODEL	DOORS	SHELVES	DIMENSIONS (WxDxH)	CAPACITY	HP	AMPS	VOLTAGE	PLUG TYPE
PMF26-1	1	2	26 4/5 x 26 x 55 7/8 in 680 x 660 x 1420 mm	8.5 cu.ft. 240 L	1/4+	4.2	115/60/1	NEMA 5-15P
PMF27-1	1	4	27 1/5 x 26 1/5 x 80 3/8 in 690 x 665 x 2040 mm	13 cu.ft. 368 L	3/4	5.3	115/60/1	NEMA 5-15P
PMF31-1	1	4	31 1/8 x 31 3/8 x 82 3/4 in 790 x 795 x 2100 mm	23 cu.ft. 648 L	3/4	7.6	115/60/1	NEMA 5-15P

Merchandising Swing Glass Door Freezer

PAGE 2 OF 2



PMF49-2



PMF53-2



PMF79-3

- ✳ Exterior: Coated steel. Black or white finish available.
 - ✳ Interior: Attractive aluminum liner with stainless steel floor.
 - ✳ Refrigeration system maintains temperatures between -8°F and 0°F (-23°C to -18°C).
 - ✳ Self-Closing double pane glass door with positive seal.
 - ✳ Shelves: Adjustable heavy-duty PVC coated shelves.
 - ✳ Leveling feet or casters are available.
- ✳ LED lighting.
 - ✳ Electronic control system makes it easy to adjust temperature set point and defrost frequency.
 - ✳ Removable installation board makes it easy to access condenser coil for cleaning and service.
 - ✳ These units use HYDRO-CARBON R290 refrigerant, which is environmentally friendly and more efficient than R134a/R404a refrigerant.

MODEL	DOORS	SHELVES	DIMENSIONS (WXDXH)	CAPACITY	HP	AMPS	VOLTAGE	PLUG TYPE
PMF49-2	2	8	49 1/5 x 26 1/5 x 80 3/8 in 1250 x 665 x 2040 mm	29 cu.ft. 830 L	3/4	9.1	115/60/1	NEMA 5-15P
PMF53-2	2	8	53 1/8 x 31 7/8 x 79 3/8 in 1350 x 810 x 2015 mm	45 cu.ft. 1270 L	1	10.6	115/60/1	NEMA 5-15P
PMF79-3	3	12	79 1/2 x 30 3/5 x 80 3/8 in 2020 x 777 x 2040 mm	52 cu.ft. 1479 L	0.75 x 2	15.6	115/60/1	NEMA 5-20P



14 / 18

AIR COOLED ICEMACHINE

Self-contained air-cooled ice machines producing half-size cubes for bars, restaurants and hotels.

PIM280-H

PIM350-H

PIM530-H

Air Cooled Ice Machine



PIM280-H



PIM350-H



PIM530-H

- ✱ Durable stainless steel exterior.
 - ✱ 280: Front-in, all side-out airflow, 350/530: left and right side-in, rear-out airflow.
 - ✱ Bright LED lights illuminate the ice bin. Removable air filter allows for quick cleaning.
 - ✱ Digital controller allows user to quickly identify issues.
- ✱ Ambient Temp Range 41 - 100°F.
 - ✱ Water Temp Range 41 - 90°F.
 - ✱ Water Pressure 18 - 80 PSI.
 - ✱ Adjustable legs.
 - ✱ HYDRO-CARBON R290 refrigerant which is environmentally friendly and more efficient.

MODEL	CONDENSER	DIMENSIONS (WXDXH, IN)	ICE PRODUCTION / DAY (AT 21°C)	BIN STORAGE (AT 10°C)	HP	ICE TYPE	VOLTAGE	NEMA CONFIG	WATER INLET
PIM280-H	Air-Cooled	26 1/9 x 27 3/5 x 38 1/5	127kg / 280 lb.	36kg / 80 lb.	3/8	Half Size Cubes	115V/60Hz	5-15P	3/4 Inches
PIM350-H	Air-Cooled	23 2/5 x 24 1/2 x 22 2/7	159kg / 380 lb.	125kg / 275 lb.	3/8	Half Size Cubes	115V/60Hz	5-15P	3/4 Inches
PIM530-H	Air-Cooled	31 2/7 x 24 1/2 x 22 2/7	240kg / 500 lb.	170kg / 375 lb.	3/4	Half Size Cubes	115V/60Hz	5-15P	3/4 Inches



15 / 18

OPEN AIR MERCHANDISER

Open-front and glass-sided air curtain merchandisers that keep grab-and-go items visible and at safe temperature with no doors to open.

POAM30

POAM36

POAM48

POAM72

POAM30G

POAM36G

POAM48G

POAM72G

Open Air Merchandiser

REFRIGERATOR WITH HYDROCARBON REFRIGERANT



- ❖ High capacity, factory balanced refrigeration system that maintains cabinet temperatures of 33°F to 41°F (0.5°C to 5°C) for the best in food preservation.
- ❖ Standard back-guard improves airflow.
- ❖ LED lighting interior.
- ❖ Energy saving night curtain standard.
- ❖ 300 series stainless steel floor.
- ❖ Foamed with polyurethane, high-density cell insulation that has zero ozone depletion potential.
- ❖ Factory installed condensate pan heater kit available if there is no access to drain plumbing.
- ❖ Adjustable shelving.
- ❖ Exterior Optional: white or stainless steel finish available.

MODEL	SHELVES	DIMENSIONS (WxDxH)	CAPACITY (CU.FT.)	HP	AMPS	VOLTAGE	NEMA CONFIG
POAM30	4	30 x 28 2/5 x 81 4/5	—	1 - 1/2	11	115V/60Hz	5-15P
POAM36	4	36 x 28 2/5 x 81 4/5	—	1 - 1/2	11	115V/60Hz	5-15P
POAM48	4	48 x 28 2/5 x 81 4/5	—	2	9.2	208-230V/60Hz	6-15P
POAM72	8	72 x 28 2/5 x 81 4/5	—	3	14.8	208-230V/60Hz	6-20P

Open Air Merchandiser

GLASS SIDED REFRIGERATOR WITH HYDROCARBON REFRIGERANT



- ❖ High capacity, factory balanced refrigeration system that maintains cabinet temperatures of 33°F to 41°F (0.5°C to 5°C) for the best in food preservation.
- ❖ Standard back-guard improves airflow.
- ❖ LED lighting interior.
- ❖ Energy saving night curtain standard.
- ❖ 300 series stainless steel floor.
- ❖ Foamed with polyurethane, high-density cell insulation that has zero ozone depletion potential.
- ❖ Factory installed condensate pan heater kit available if there is no access to drain plumbing.
- ❖ Adjustable shelving.
- ❖ Exterior Optional: white or stainless steel finish available.

MODEL	SHELVES	DIMENSIONS (WxDxH)	CAPACITY (CU.FT.)	HP	AMPS	VOLTAGE	NEMA CONFIG
POAM30G	4	30 x 28 2/5 x 81 4/5	—	1 - 1/2	11	115V/60Hz	5-15P
POAM36G	4	36 x 28 2/5 x 81 4/5	—	1 - 1/2	11	115V/60Hz	5-15P
POAM48G	4	48 x 28 2/5 x 81 4/5	—	2	9.2	208-230V/60Hz	6-15P
POAM72G	8	72 x 28 2/5 x 81 4/5	—	3	14.8	208-230V/60Hz	6-20P



16 / 18

REFRIGERATED CAKE DISPLAY CASE

Curved-glass bakery display cases with tempered glass shelves, in 2-shelf and 3-shelf configurations for maximum product visibility.

PCD36-2

PCD47-2

PCD59-2

PCD71-2

PCD36-3

PCD47-3

PCD59-3

PCD71-3

Refrigerated Cake Display Case

2-SHELF



PCD36-2



PCD47-2



PCD59-2



PCD71-2

- ❖ Refrigeration system maintains temperatures between 36°F and 43°F (2°C to 6°C).
- ❖ Exterior: Stainless steel floor and walls, standard.
- ❖ Sliding doors.
- ❖ 12V LED lighting system, safe for users to operate.
- ❖ Tempered glass to avoid injury by broken glass.
- ❖ Preinstalled hidden caster design.

- ❖ NSF-7 compliant for open food product.
- ❖ Shelves: Adjustable glass shelves provide extra large viewing area to maximize bakery product presentation.
- ❖ Electronic control system makes it easy to adjust temperature set point and defrost frequency.
- ❖ Removable installation board makes it easy to access condenser coil for cleaning and service.
- ❖ Option of HYDRO-CARBON R290 refrigerant available.

MODEL	DOORS	SHELVES	DIMENSIONS (WxDxH)	CAPACITY	HP	AMPS	VOLTAGE	PLUG TYPE
PCD36-2	2	2	35 3/8 x 28 3/4 x 47 1/4 in 900 x 730 x 1200 mm	11.3 cu.ft. 320 L	1/3+	4.8	115/60/1	NEMA 5-15P
PCD47-2	2	2	47 1/4 x 28 3/4 x 47 1/4 in 1200 x 730 x 1200 mm	14 cu.ft. 400 L	1/3+	5.58	115/60/1	NEMA 5-15P
PCD59-2	2	2	59 1/8 x 28 3/4 x 47 1/4 in 1500 x 730 x 1200 mm	17.7 cu.ft. 500 L	1/2+	9.96	115/60/1	NEMA 5-15P
PCD71-2	2	2	70 7/8 x 28 3/4 x 47 1/4 in 1800 x 730 x 1200 mm	21.2 cu.ft. 600 L	1/2+	11.04	115/60/1	NEMA 5-15P

Refrigerated Cake Display Case

3-SHELF



PCD36-3

PCD47-3

PCD59-3

PCD71-3

- ✱ Refrigeration system maintains temperatures between 36°F and 43°F (2°C to 6°C).
 - ✱ Exterior: Stainless steel floor and walls, standard.
 - ✱ Sliding doors.
 - ✱ 12V LED lighting system, safe for users to operate.
 - ✱ Tempered glass to avoid injury by broken glass.
 - ✱ Preinstalled hidden caster design.
- ✱ NSF-7 compliant for open food product.
 - ✱ Shelves: Adjustable glass shelves provide extra large viewing area to maximize bakery product presentation.
 - ✱ Electronic control system makes it easy to adjust temperature set point and defrost frequency.
 - ✱ Removable installation board makes it easy to access condenser coil for cleaning and service.
 - ✱ Option of HYDRO-CARBON R290 refrigerant available.

MODEL	DOORS	SHELVES	DIMENSIONS (WxDxH)	CAPACITY	HP	AMPS	VOLTAGE	PLUG TYPE
PCD36-3	2	3	35 3/8 x 28 3/4 x 55 1/8 in 900 x 730 x 1400 mm	12.7 cu.ft. 360 L	1/3+	4.8	115/60/1	NEMA 5-15P
PCD47-3	2	3	47 1/4 x 28 3/4 x 55 1/8 in 1200 x 730 x 1400 mm	19.4 cu.ft. 550 L	1/3+	9.66	115/60/1	NEMA 5-15P
PCD59-3	2	3	59 1/8 x 28 3/4 x 55 1/8 in 1500 x 730 x 1400 mm	25 cu.ft. 700 L	1/2+	9.96	115/60/1	NEMA 5-15P
PCD71-3	2	3	70 7/8 x 28 3/4 x 55 1/8 in 1800 x 730 x 1400 mm	30 cu.ft. 850 L	1/2+	11.04	115/60/1	NEMA 5-15P



17 / 18

MILK COOLER

Cold-wall milk coolers with white-coated steel exteriors and a centrally located floor drain for easy cleaning.

PMC34

PMC49

PMC58

Milk Cooler



PMC34



PMC49



PMC58

- ✦ Cabinet finish: White-coated steel exterior with stainless steel lid and door with lock and latch. Interior is NSF approved white aluminum liner with stainless steel floor.
 - ✦ Option of all stainless steel exterior available.
 - ✦ Heavy duty construction: CFC and HCFC-free foamed-in-place polyurethane insulation.
 - ✦ Refrigeration system: Single access, cold wall milk coolers maintain milk temperature of 33°F - 38°F (0.5°C - 3.3°C).
 - ✦ Preinstalled heavy-duty casters with brakes.
- ✦ Electronic control system makes it easy to adjust temperature set point.
 - ✦ Bottom floor drain is centrally located for easy cleaning, connecting to drain hose with hose adapter.
 - ✦ Removable installation board makes it easy to access condenser coil for cleaning and service.
 - ✦ These units use HYDRO-CARBON R290 refrigerant, which is environmentally friendly and more efficient than R134a/R404a refrigerant.

MODEL	DOORS	DIMENSIONS (WXDXH)	CAPACITY (13X13X11 CASES)	CAPACITY (19X13X11 CASES)	HP	AMPS	VOLTAGE	PLUG TYPE
PMC34	2	34 x 30 3/5 x 40 in 864 x 778 x 1052 mm	8	4	1/5	2.28	115/60/1	NEMA 5-15P
PMC49	2	49 x 30 3/5 x 40 in 1245 x 778 x 1052 mm	12	8	1/5	2.28	115/60/1	NEMA 5-15P
PMC58	2	58 x 30 3/5 x 40 in 1475 x 778 x 1052 mm	16	10	1/5	2.4	115/60/1	NEMA 5-15P



18 / 18

OUTDOOR RATED SMALL REFRIGERATOR

A compact, outdoor-rated undercounter refrigerator for patios and outdoor kitchens, with no plumbing required.

POR23-1

Outdoor Rated Small Refrigerator



POR23-1

- ❖ Stainless steel interior and exterior. Option of bright white aluminum interior available.
 - ❖ Refrigeration system keeps food at safe temperatures between 33°F and 40°F (0.5°C to 5°C).
 - ❖ Stainless steel heavy-duty door with enduring quality. Locks and keys included.
- ❖ Simple installation with no plumbing required.
 - ❖ Electronic control system makes it easy to adjust temperature set point and defrost frequency.
 - ❖ Preinstalled heavy-duty casters.
 - ❖ GN1/1 pan is suitable.
 - ❖ Shelves: Adjustable heavy-duty PVC coated shelves.

MODEL	DOORS	SHELVES	DIMENSIONS (WxDXH)	CAPACITY	HP	AMPS	VOLTAGE	PLUG TYPE
POR23-1	1	2	23 2/5 x 24 3/4 x 32 3/4 in 595 x 628 x 830 mm	5.7 cu.ft. 161 L	1/6	2.2	115/60/1	NEMA 5-15P

PRIME GLOBAL PARTNERS



PRIME GLOBAL PARTNERS

www.pgpsupply.com

sales@pgpsupply.com

Private-label sourcing, product development and brand-building for foodservice equipment distributors.



Prefer not to build your own brand? We also supply under our own Prime Refrigeration product line.